

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 1 061 465 A2**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:

20.12.2000 Bulletin 2000/51

(51) Int Cl.7: **G06F 17/60**(21) Application number: **00305103.4**(22) Date of filing: **16.06.2000**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**

Designated Extension States:

**AL LT LV MK RO SI**(30) Priority: **17.06.1999 US 335287**

(71) Applicant: **International Business Machines  
Corporation**  
**Armonk, NY 10504 (US)**

(72) Inventors:

- **Berstis, Viktors, IBM United Kingdom Ltd.  
Winchester, Hampshire SO21 2JN (GB)**
- **Rodriguez, Herman, IBM United Kingdom Ltd.  
Winchester, Hampshire SO21 2JN (GB)**

(74) Representative: **Waldner, Philip**  
**IBM United Kingdom Limited,**  
**Intellectual Property Department,**  
**Hursley Park**  
**Winchester, Hampshire SO21 2JN (GB)**

(54) **Method and apparatus for providing reduced cost online service and adaptive targeting of advertisements**

(57) A method and apparatus for adaptively targeting advertisements to a specific client computer from a server within a distributed data processing system is provided. As a user of the client browses the World Wide Web, the material that is downloaded to the client constitutes a datastream. At some location during the routing of the datastream, either on the server or at the client, the datastream is scanned to generate a list of keywords that are present within the datastream. The datastream may be analyzed in real-time or cached and analyzed on a delayed basis. The generated list of keywords represents a summary of the content that appears to be the focus of interest of the user. The key-

words are compared against a database of advertisements, and the server selects an advertisement that matches the user's area of interest in comparison to the analysis of the user's browsing history. The selected advertisement is then inserted into the datastream to be routed to the client. In consideration for viewing targeted advertisements and to entice a Web viewer to allow the monitoring of a datastream so that targeted advertisements may be placed into the datastream, a Web viewer may receive online connection service for free, for a reduced cost, at a premium level of service, or for other some other value, such as frequent viewer credits that may be exchanged for goods and services.




FIG. 4

## Description

### BACKGROUND OF THE INVENTION

#### 1. Technical Field:

[0001] The present invention relates generally to an improved data processing system and, in particular, to a method and apparatus for monitoring and processing a datastream during a commercial network connection.

#### 2. Description of Related Art:

[0002] The World Wide Web (WWW, also known simply as "the Web") is an abstract cyberspace of information that is physically transmitted across the hardware of the Internet. In the Web environment, servers and clients communicate using Hypertext Transport Protocol (HTTP) to transfer various types of data files. Much of this information is in the form of Web pages identified by unique Uniform Resource Locators (URLs) or Uniform Resource Identifiers (URIs) that are hosted by servers on Web sites. The Web pages are often formatted using Hypertext Markup Language (HTML), which is a file format that is understood by software applications, called Web browsers. A browser requests the transmission of a Web page from a particular URL, receives the Web page in return, parses the HTML of the Web page to understand its content and presentation options, and displays the content on a computer display device. By using a Web browser, a user may navigate through the Web using URLs to view Web pages.

[0003] As the Web continues to increase dramatically in size, corporations and organizations have attempted to promote themselves as Web portals or, following the analogy of the Internet and the Web has being an information superhighway, as an on-ramp to the Web. By indexing and collecting vast amounts of information resources within one Web site, a Web portal attempts to become a user's favorite Web starting point for each navigation session of the Web. A user, knowing that he may be able to find almost all desired information within a single Web site, may prefer to search and browse through the Web portal. A Web portal gains a commercial advantage through increased viewership by receiving more advertisement revenue per Web page viewed. However, in its attempt to attract as many users as possible, Web portals increasingly gather together a vast quantity of disparate content. The publication of Web pages is an unrestricted and uncoordinated process. The latest news, book reviews, amateur poetry, games, research, stock and bond prices quotes, chat rooms, groups, clubs, shareware, technical support, on-line shopping, etc., may be found on the Web. There is no ability to know beforehand the type of content that drew the user to the Web portal.

[0004] While browsing the Web, a user may follow a hyperlink from one Web page to another Web page. The

user may not know what type of content will be viewed upon the target or destination of the hyperlink because hyperlinks are usually small images or very short text strings that provide only a term or a few words that may interest the user based on the context of the surrounding material. The content of the presented hyperlink is often a text string that merely provides the URL of the destination Web page, and the URL is arbitrarily defined by the Web master of a Web site or by the author of the Web page. Hence, a user may follow a hyperlink without knowing what material is being retrieved, and the datastream of downloaded material may be difficult to classify within a category of subject matter.

[0005] A significant number of commercial Web sites lose money, and if the Web site generates a profit, the source of the profits are usually advertising revenues. Providing advertisement space on Web pages was one of the first moneymaking opportunities for owners of commercial Web sites or authors of Web pages. Banner advertisements at the top of Web pages are now ubiquitous. Commercial Web sites rely on such advertisements to generate positive income, and advertisers rely on this Web space for the opportunity to create brand-name recognition for their products and services. As noted above, Web portals attempt to increase their advertisement revenue by increasing the number of viewed Web pages, so called "eyeball count".

[0006] Advertisers also desire to pay for advertisement placement based on the demographics of Web viewers. However, many Web portals and Internet Service Providers (ISPs) protect user privacy and do not collect biographical or demographic information from the users that surf the various Web sites on their servers or across their domains. Hence, it is difficult for advertisers to target their advertisement expenditures based on Web viewer demographics. Advertisers may also desire to target advertisement expenditures indirectly based on the content being viewed and downloaded by the viewers of a Web page or Web portal. However, because Web portals gather disparate content, it is difficult to ascertain the reasons why a user may be viewing particular content.

[0007] This situation is unlike placing advertisements on cable or network television. In that case, informational program guides about the content being carried on the various channels is widely disseminated well ahead of the time of broadcast of the content. Television viewers are enticed to watch programs containing definable content. Based on consumer research, advertisers can ascertain which demographic segment of a population may be attracted to the content being displayed on the channel. Based on the resulting research data, advertisers will target particular advertisements to particular segments of the population based on the content of the broadcast.

[0008] In the case of many Web viewers accessing and downloading content from a Web site or Web server, advertisers may have a comparatively difficult time tar-

getting each viewer with effective advertisements so that the advertiser's expenditures are used wisely. In addition to targeting advertisements once a person is viewing Web content, advertisers require a method for enticing Web viewers to view advertisements in a manner similar to enticing television viewers to view particular television program content and, hence, particular advertisements placed in that content.

[0009] Therefore, it would be useful to have a method for directing advertisements to particular segments of users that download material from particular Web portals in order to increase the efficiency of advertisement expenditures. It would be particularly advantageous to target each user uniquely without gathering biographical information about each particular user. It would also be advantageous to entice Web viewers to view particular advertisements.

### SUMMARY OF THE INVENTION

[0010] According to a first aspect of the invention there is provided a method for providing online connection service from a server to a client in a distributed data processing system, the method comprising the computer-implemented steps of: inserting selected advertisements into a datastream for a session connecting the server with the client; and reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream.

[0011] According to a second aspect of the invention there is provided a method for sending advertisements from a server to a client in a distributed data processing system, the method comprising the computer-implemented steps of: scanning, on the server, a datastream for a session connecting the server with the client; generating a list of keywords from content within the datastream; selecting advertisements based on the generated keyword list; and inserting the selected advertisements into the datastream.

[0012] According to a third aspect of the invention there is provided a distributed data processing system for providing online connection service from a server to a client, the distributed data processing system comprising: inserting means for inserting selected advertisements into a datastream for a session connecting the server with the client; and reducing means for reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream.

[0013] According to a fourth aspect of the invention there is provided a distributed data processing system for sending advertisements from a server to a client, the distributed data processing system comprising: scanning means for scanning, on the server, a datastream for a session connecting the server with the client; generating means for generating a list of keywords from content within the datastream; selecting means for selecting advertisements based on the generated keyword

list; and inserting means for inserting the selected advertisements into the datastream.

[0014] According to a fifth aspect of the invention there is provided a distributed data processing system for receiving advertisements at a client from a server, the distributed data processing system comprising: scanning means for scanning, on the client, a datastream for a session connecting the client with the server; generating means for generating a list of keywords from content within the datastream; sending means for sending the generated list of keywords to the server; and receiving means for receiving advertisements within the datastream, wherein the advertisements comprise content semantically related to the generated list of keywords.

[0015] According to a sixth aspect of the invention there is provided a computer program product in a computer readable medium for use in a distributed data processing system for providing online connection service from a server to a client, the computer program product comprising: first instructions for inserting selected advertisements into a datastream for a session connecting the server with the client; and second instructions for reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 is a pictorial representation of a distributed data processing system in which the present invention may be implemented;

Figure 2 is a block diagram depicting a data processing system, which may be implemented as a server in accordance with a preferred embodiment of the present invention;

Figure 3 is a block diagram illustrating a data processing system which may be implemented as a client in accordance with a preferred embodiment of the present invention;

Figure 4 is a flowchart depicting a distributed data processing system for adaptively targeting advertisements for a client using a datastream scanner within the server;

Figure 5 is a block diagram depicting a distributed data processing system that adaptively targets ad-

vertisements for a client by scanning the datastream addressed to the client with a data processing unit within the client itself;

**Figure 6** is a flowchart depicting a process in which a client receives a datastream containing adaptively targeted advertisements;

**Figure 7** is a flowchart depicting the processing performed by a server that scans a datastream in order to insert adaptively targeted advertisements addressed to a client;

**Figure 8** is a flowchart describing a process in which a client scans an incoming datastream addressed to the client in order to generate browse history information that is transmitted back to a server;

**Figure 9** is a flowchart depicting a process in which a server receives browse history information from a client and inserts adaptively targeted advertisements into the datastream sent back to the client;

**Figure 10** is a flowchart depicting the process by which a server selects adaptively targeted advertisements based on the browsing history of a client; and

**Figure 11** is a flowchart depicting a process by which a server receives electronically published advertisements and processes these advertisements so that they may be retrieved at some later point as adaptively targeted advertisements.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0017] With reference now to the figures, **Figure 1** depicts a pictorial representation of a distributed data processing system in which the present invention may be implemented. Distributed data processing system **100** is a network of computers in which the present invention may be implemented. Distributed data processing system **100** contains a network **102**, which is the medium used to provide communications links between various devices and computers connected together within distributed data processing system **100**. Network **102** may include permanent connections, such as wire or fiber optic cables, or temporary connections made through telephone connections.

[0018] In the depicted example, a server **104** is connected to network **102** along with storage unit **106**. In addition, clients **108**, **110**, and **112** also are connected to a network **102**. These clients **108**, **110**, and **112** may be, for example, personal computers or network computers. For purposes of this application, a network computer is any computer, coupled to a network, which re-

ceives a program or other application from another computer coupled to the network. In the depicted example, server **104** provides data, such as boot files, operating system images, and applications to clients **108-112**. Clients **108**, **110**, and **112** are clients to server **104**. Distributed data processing system **100** may include additional servers, clients, and other devices not shown. In the depicted example, distributed data processing system **100** is the Internet with network **102** representing a worldwide collection of networks and gateways that use the TCP/IP suite of protocols to communicate with one another. At the heart of the Internet is a backbone of high-speed data communication lines between major nodes or host computers, consisting of thousands of commercial, government, educational and other computer systems that route data and messages. Of course, distributed data processing system **100** also may be implemented as a number of different types of networks, such as for example, an intranet, a local area network (LAN), or a wide area network (WAN). **Figure 1** is intended as an example, and not as an architectural limitation for the present invention.

[0019] Referring to **Figure 2**, a block diagram depicts a data processing system, which may be implemented as a server, such as server **104** in **Figure 1**, in accordance with a preferred embodiment of the present invention. Data processing system **200** may be a symmetric multiprocessor (SMP) system including a plurality of processors **202** and **204** connected to system bus **206**. Alternatively, a single processor system may be employed. Also connected to system bus **206** is memory controller/cache **208**, which provides an interface to local memory **209**. I/O bus bridge **210** is connected to system bus **206** and provides an interface to I/O bus **212**. Memory controller/cache **208** and I/O bus bridge **210** may be integrated as depicted.

[0020] Peripheral component interconnect (PCI) bus bridge **214** connected to I/O bus **212** provides an interface to PCI local bus **216**. A number of modems may be connected to PCI bus **216**. Typical PCI bus implementations will support four PCI expansion slots or add-in connectors. Communications links to network computers **108-112** in **Figure 1** may be provided through modem **218** and network adapter **220** connected to PCI local bus **216** through add-in boards.

[0021] Additional PCI bus bridges **222** and **224** provide interfaces for additional PCI buses **226** and **228**, from which additional modems or network adapters may be supported. In this manner, server **200** allows connections to multiple network computers. A memory-mapped graphics adapter **230** and hard disk **232** may also be connected to I/O bus **212** as depicted, either directly or indirectly.

[0022] Those of ordinary skill in the art will appreciate that the hardware depicted in **Figure 2** may vary. For example, other peripheral devices, such as optical disk drives and the like, also may be used in addition to or in place of the hardware depicted. The depicted example

is not meant to imply architectural limitations with respect to the present invention.

[0023] The data processing system depicted in **Figure 2** may be, for example, an IBM RISC/System 6000 system, a product of International Business Machines Corporation in Armonk, New York, running the Advanced Interactive Executive (AIX) operating system.

[0024] With reference now to **Figure 3**, a block diagram illustrates a data processing system in which the present invention may be implemented. Data processing system **300** is an example of a client computer. Data processing system **300** employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures such as Micro Channel and ISA may be used. Processor **302** and main memory **304** are connected to PCI local bus **306** through PCI bridge **308**. PCI bridge **308** also may include an integrated memory controller and cache memory for processor **302**. Additional connections to PCI local bus **306** may be made through direct component interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **310**, SCSI host bus adapter **312**, and expansion bus interface **314** are connected to PCI local bus **306** by direct component connection. In contrast, audio adapter **316**, graphics adapter **318**, and audio/video adapter **319** are connected to PCI local bus **306** by add-in boards inserted into expansion slots. Expansion bus interface **314** provides a connection for a keyboard and mouse adapter **320**, modem **322**, and additional memory **324**. SCSI host bus adapter **312** provides a connection for hard disk drive **326**, tape drive **328**, and CD-ROM drive **330**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

[0025] An operating system runs on processor **302** and is used to coordinate and provide control of various components within data processing system **300** in **Figure 3**. The operating system may be a commercially available operating system such as OS/2, which is available from International Business Machines Corporation. "OS/2" is a trademark of International Business Machines Corporation. An object oriented programming system such as Java may run in conjunction with the operating system and provides calls to the operating system from Java programs or applications executing on data processing system **300**. "Java" is a trademark of Sun Microsystems, Inc. Instructions for the operating system, the object-oriented operating system, and applications or programs are located on storage devices, such as hard disk drive **326**, and may be loaded into main memory **304** for execution by processor **302**.

[0026] Those of ordinary skill in the art will appreciate that the hardware in **Figure 3** may vary depending on the implementation. Other internal hardware or peripheral devices, such as flash ROM (or equivalent nonvolatile memory) or optical disk drives and the like, may be used in addition to or in place of the hardware depicted

in **Figure 3**. Also, the processes of the present invention may be applied to a multiprocessor data processing system.

[0027] For example, data processing system **300**, if optionally configured as a network computer, may not include SCSI host bus adapter **312**, hard disk drive **326**, tape drive **328**, and CD-ROM **330**, as noted by dotted line **332** in **Figure 3** denoting optional inclusion. In that case, the computer, to be properly called a client computer, must include some type of network communication interface, such as LAN adapter **310**, modem **322**, or the like. As another example, data processing system **300** may be a stand-alone system configured to be bootable without relying on some type of network communication interface, whether or not data processing system **300** comprises some type of network communication interface. As a further example, data processing system **300** may be a Personal Digital Assistant (PDA) device which is configured with ROM and/or flash ROM in order to provide nonvolatile memory for storing operating system files and/or user-generated data.

[0028] The depicted example in **Figure 3** and above-described examples are not meant to imply architectural limitations.

[0029] With reference now to **Figure 4**, a flowchart depicts a distributed data processing system for adaptively targeting advertisements for a client using a datastream scanner within the server. Distributed data processing system **400** contains client **402** running browser application **404** that generates HTTP requests **406** that are sent to server **408**. Client requests that are addressed to other servers on the Internet are routed to the Internet through interface **410**. If server **408** is able to fulfill the HTTP request message without routing the message to another server on the Internet, server **408** may access its own internal database and generate an HTTP response that is sent to client **402**. Otherwise, server **408** receives data from the Internet at physical interface **412** and eventually routes this data to client **402** as HTTP response **414**.

[0030] Distributed data processing system **400** receives electronically published advertisements from various customers and stores these advertisements in unprocessed advertisements database **416**. Advertisement processing unit **418** retrieves the advertisements from unprocessed advertisements database **416**, processes these advertisements, and stores these advertisements in categorized advertisements database **420**. The advertisements are processed by scanning the advertisements for keywords that convey the gist of the content of each of the advertisements. These keyword lists are associatively stored with the advertisements in categorized advertisements database **420**.

[0031] Information about the advertisers may be stored in advertiser database **421**. Rather than determining the gist of the content of each advertisement from the subject matter within the advertisement, an advertiser may provide a set of keywords that capture a

wider context in which the advertiser believes the advertiser's product or service belongs. For example, a car manufacturer may create an advertisement for an automobile that does not use the words "car", "vehicle", or "automobile." Thus, if a keyword list was generated from the content of the advertisement, the generated keyword list may not capture or convey the context in which the advertiser would desire to have the automobile advertisement displayed. Hence, the advertiser may create a keyword list for a complete category of products or services that target a particular demographic or particular types of datastreams without relying on a keyword list generated from the advertisement's content. In this manner, the advertiser may target an automobile advertisement to someone that is browsing the Web for certain types of luxury goods.

[0032] Server 408 receives a datastream from the Internet that is directed or addressed to client 402 and is responsible for routing the datastream to the client. However, in a system that incorporates the present invention, server 408 processes the datastream to some extent before routing the datastream to client 402. Datastream scanner unit 422 scans the content of the datastream and generates browse history information 424 that is sent to advertisement selector unit 426. The content of the datastream comprises URIs and other information with HTTP messages, File Transport Protocol (FTP) packets, TCP/IP packets, etc. Alternatively, datastream scanner unit 422 may work in conjunction with optional upstream scanner unit 423 that scans the HTTP request messages from the client. Information concerning the client requests may be combined with the information gleaned from the downloaded datastream, and the combined information may be forwarded to advertisement selector unit 426.

[0033] Advertisement selector unit 426 also receives session characterization information 428 containing information about a particular session or connection between server 408 and client 402. In other words, as a connection is made between the client and the server, information is stored and controlled by the server that describes various parameters about the connection. The session characterization information may include different types of information, such as: the type of computer platform that is being utilized as the client computer; the type and version number of client software or browser software that is being used to receive the downloaded datastream; the current time of day for the session between the client and the server; the current season of the year in which the session is being held; the amount of available connection bandwidth for the session; the effective download speed of the client; the amount of connection time for the session; the number of bytes, the number of Web pages, the number of files, or other content metrics concerning the material that has been downloaded to the client; a list of advertisements inserted into the monitored datastream; the number of advertisements either sent or targeted to the client; and

the geographic location of the client. Advertisement inserter unit 430 scans and monitors the datastream addressed to client 402 to determine appropriate points in the datastream for inserting adaptively targeted advertisements to the user of browser application 404. Advertisement inserter unit 430 generates a request that is sent to advertisement selector unit 426.

[0034] Advertisement selector unit 426 uses browse history information 424 and session characterization information 428 to select an adaptively targeted advertisement from categorized advertisements database 420. If advertisement selector unit 426 decides that categorized advertisements database 420 does not have a suitable advertisement for a relative match with browse history information 424 and session characterization information 428, advertisement selector unit 426 may select an advertisement from advertiser database 421.

[0035] Advertisement selector unit 426 sends the selected advertisement to advertisement inserter unit 430, which places the advertisement into the appropriate point in the datastream and forwards the modified datastream or HTTP response message to datastream scanner unit 422.

[0036] In this manner, datastream scanner unit 422, advertisement selector unit 426, and advertisement inserter unit 430 work in conjunction to monitor the datastream directed or requested by the user of browser application 404 so that server 408 may determine appropriate points within the datastream for insertion of target advertisements and then placing carefully selected advertisements in those locations within the datastream. The datastream may be stored as a cached datastream so that datastream scanner unit 422 does not scan in real-time while the datastream is flowing through the server. At appropriate or predetermined intervals, datastream scanner unit 422 reports the browse history information using statistics gathered from the cached datastream. The choice of using a cached datastream may depend upon the processing speed of datastream scanner unit 422, the bandwidth of the datastream, etc.

[0037] The relative placement of advertisement inserter unit 430 and datastream scanner unit 422 at successive positions along the datastream, may be reversed without affecting the ability of server 408 to selectively target advertisements to a client system. In the example shown, advertisement inserter unit 430 places selected advertisements within the datastream that is then scanned by datastream scanner unit 422. By placing the advertisements into the datastream before the datastream is scanned, the advertisement that has been placed into the datastream becomes part of browse history information 424. If the inserted advertisement is properly selected by advertisement selector unit 426, the inserted advertisement will blend with the content of the datastream so that the advertisement does not skew the results generated by datastream scanner unit 422. If it is determined by the empirical results that the insertion of advertisements into the datastream skew the

generated results from the scan of the datastream, a feedback mechanism may be employed in which advertisement selector unit 426 also provides the selected advertisement to datastream scanner unit 422 so that the insertion of an advertisement into the datastream does not skew the scanned results generated by datastream scanner unit 422.

[0038] In an alternative embodiment, datastream scanner unit 422 scans the datastream before the insertion of an advertisement by advertisement inserter unit 430. In this case, the results generated by datastream scanner unit 422 will represent the content actually requested by the user of browser application 404, i.e., the generated results will represent the datastream without advertisements. However, in situations in which advertisements constitute a large percentage of the volume of the data in the datastream addressed to client 402, the generated results may represent only a small portion of the datastream. In other words, if the user of browser application 404 is browsing through Web pages that contain a lot of advertisements, and many advertisements are being inserted into the datastream, then the generated results of datastream scanner unit 422 may not accurately represent the content of the advertisements in the browsed history information 424.

[0039] Underlying the ability to direct targeted advertisements to a viewer is the assumption that a user may have agreed to receive such advertisements in return for some type of valuable consideration. At some prior point in time, the viewer has set up an account with an online service provider, or Internet service provider (ISP), or the equivalent. At that time, the viewer may have been informed that the ISP would provide an incentive to the viewer to receive targeted advertisements. The viewer may accept or decline the offer at that time, but the viewer may change this preference at some time in the future, either by selecting a function within the browser that notifies the server that the viewer has changed this preference or by submitting an electronic form or Web page to notify the server of the change in preference. The viewer may toggle this preference on/off multiple times during a single session through a configuration request.

[0040] Upstream scanner unit 423 may monitor the incoming messages from the client for configuration requests from the client. The server uses these configuration requests as part of the session characterization information in order to determine whether to place targeted advertisements into the viewer's datastream.

[0041] In return for receiving these advertisements, the viewer may receive free connection time from the ISP, which the ISP can provide because the ISP collects revenue from advertisers who expect that the ISP will provide a service for adaptively targeting these advertisements to viewers. The ISP earns a profit because the revenue from the advertisers is greater than the connection fees that could be collected from the viewers that connect to the ISP.

[0042] The fee schedule between the ISP and the viewer may be an all-or-nothing arrangement or a graduated scale. The viewer may receive free connection time in return for receiving only targeted advertisements. Alternatively, the viewer may receive some value for receiving a certain number of targeted advertisements, and the viewer receives more value for a larger number of viewed advertisements. By monitoring the number of advertisements that the server has transmitted to the client or by monitoring the amount of time that the viewer has been connected while viewing targeted advertisements, the ISP can appropriately compute the monetary value to be credited to the viewer's account. The number of targeted advertisements that have been sent to the client can be used as part of the session characterization information. For example, a viewer may receive connection time at a reduced cost that is inversely proportional to the number of viewed advertisements. As more advertisements are viewed, the ISP gradually reduces the cost for the viewer's next month of online connection time through the ISP.

[0043] In lieu of receiving reduced cost connection time, a viewer may receive frequent viewer credits that may be exchanged for goods or services. The viewer may exchange the credits for goods or services from a particular advertiser in return for viewing advertisements from the advertiser, or the viewer may exchange the credits for goods and services from the ISP.

[0044] With reference now to Figure 5, a block diagram depicts a distributed data processing system that adaptively targets advertisements for a client by scanning the datastream addressed to the client with a data processing unit within the client itself. Distributed data processing system 500 contains client 502 running browser application 504 that generates HTTP requests 506 that are sent to server 508. Client requests that are addressed to other servers on the Internet are routed to the Internet through interface 510. If server 508 is able to fulfill the HTTP request message without routing the message to another server on the Internet, server 508 may access its own internal database and generate an HTTP response that is sent to client 502. Otherwise, server 508 receives data from the Internet at physical interface 512 and eventually routes this data to client 502 as HTTP response 514.

[0045] Distributed data processing system 500 receives electronically published advertisements from various customers and stores these advertisements in unprocessed advertisements database 516. Advertisement processing unit 518 retrieves the advertisements from unprocessed advertisements database 516, processes these advertisements, and stores these advertisements in categorized advertisements database 520. Advertiser database 521 stores information about the advertisers in a manner similar to advertiser database 421, described with respect to Figure 4.

[0046] As previously described above, the location of advertisement inserter unit 430 and datastream scanner



unit 422 respectively along the data flow path for the datastream addressed to client 402 may be reversed or separated without affecting the ability of server 408 to adaptively target advertisements to the user of browser application 404 in Figure 4. Figure 5 describes an example in which the present invention is partially embedded within browser application 504 in client 502.

[0047] The function of scanning the datastream directed to the user of browser application 504 is performed by datastream scanner unit 534. Datastream scanner unit 534 scans the datastream to generate browse history information concerning the content received at client 502 from the browsing activities of the user. The browse history information generated by datastream scanner unit 534 is pushed to server 508 by browser 504. The periodicity of the push events may depend on the amount of data downloaded by client 502, the bandwidth limitations of client 502, a predetermined schedule set by server 508 for receiving the browse history information, etc.

[0048] Once server 508 receives HTTP and browse history information 506, server 508 routes HTTP request onto the Internet while keeping browse history information 532 that is filtered by optional upstream scanner unit 523 which scans the incoming requests from the client. Browse history information 532 may be embedded in HTTP messages or embedded in some other type of data packet communicated to server 508 in a variety of different protocols. Upstream scanner unit 523 directs browse history information 532 to advertisement selector unit 526 that processes and stores browse history information 532 for each session or connection to server 508. Advertisement selector unit 526 also receives session characterization information 528 that describes each particular session currently being served by server 508. Advertisement inserter unit 530 scans and monitors the datastream addressed to client 502. At appropriate locations within the datastream, advertisement inserter unit 530 determines that an adaptively targeted advertisement should be placed into the datastream and requests an advertisement from advertisement selector unit 526.

[0049] Advertisement selector unit 526 uses browse history information 532 and session characterization information 528 to select an advertisement from characterized advertisement database 520. Advertisement selector unit 526 then sends the selected advertisement to advertisement inserter unit 530 so that the selected advertisement may be inserted into the datastream and addressed to client 502. If advertisement selector unit 526 decides that categorized advertisements database 520 does not have a suitable advertisement for a relative match with browse history information 524 and session characterization information 528, advertisement selector unit 526 may select an advertisement from advertiser database 521.

[0050] In this manner, datastream scanner unit 534, advertisement inserter unit 530, and advertisement se-

lector unit 526 collaborate to monitor the content of the datastream directed to the user of browser application 504. The results of the monitoring of the datastream are pushed from the client to the server. The server then selects an advertisement that will be specifically targeted to the user of a browser application on the client in a manner such that the advertisement appears relevant to the content of the rest of the datastream being viewed by the user.

[0051] In an alternative embodiment, the advertisement inserter unit 530 may embed additional advertisements into the datastream other than the advertisements that are to be immediately shown to the viewer at the client in the current Web page. These additional advertisements may be placed within special markup tags that are not displayed by the browser on the client. The additional advertisements are cached, however, with the other material constituting the Web page. During periods of inactivity or idle periods during which the viewer is not actively using the browser, these advertisements may be shown by the browser on the display device of the client.

[0052] With reference now to Figure 6, a flowchart depicts a process in which a client receives a datastream containing adaptively targeted advertisements. Figure 6 may perform processing on the client as shown previously with respect to client 402 in Figure 4. The process begins when a user of a browser application selects a hyperlink or inputs a Uniform Resource Identifier (URI) into the client browser (step 602). The client then sends HTTP request messages to the server (step 604). At some point, the client receives HTTP response messages from the server in response to the previously transmitted HTTP request messages, and these HTTP response messages contain adaptively targeted advertisements (step 606). The client browser then displays the user requested information with these advertisements (step 608).

[0053] With reference now to Figure 7, a flowchart depicts the processing performed by a server that scans a datastream in order to insert adaptively targeted advertisements addressed to a client. Figure 7 shows processing that may be performed on a server similar to server 408 in Figure 4. The process begins when the server receives HTTP request messages from a client (step 702). The server routes the HTTP request messages onto the Internet if necessary (step 704). Some HTTP requests may be directed to URIs within or serviced by the server, in which case the server may provide the information directly without routing the HTTP request onto the Internet. The server receives HTTP response messages that are to be routed to the client in response to the previously routed HTTP request messages (step 706). The server then inserts adaptively targeted advertisements into appropriate locations within the HTTP response messages that constitute the datastream addressed to the client (step 708). A datastream scanner unit within the server scans the data-



ream for keywords in order to generate a user session specific list of keywords (step 710).

[0054] The datastream scanner unit may generate a list of keywords in a variety of manners. Although the method generally entails scanning the datastream for a set of keywords and compiling a count of the individual keywords, several different criteria or statistical methods may be applied to the occurrence counts to determine which keywords should be included as a representative set of keywords for the browse history information. An important point is that many different types and sets of rules may be applied to the analysis of the datastream in order to determine a general trend of interest of the user in the material being viewed. Over time, this analysis will generate a shifting set of keywords to be included as relevant information in the browse history information.

[0055] One method of generating a list of keywords encompasses using a moving window of content for analysis within the datastream. In other words, a certain subset of the datastream is analyzed to generate the necessary list of keywords. This moving window of content may be determined in several ways. The first method of determining the moving window of content is to analyze a predetermined number of downloaded Web pages as the window of content that should be analyzed by the datastream scanner unit. As time passes by, the window of content is a predetermined number of the most recently downloaded Web pages. A second method of determining the size of the moving window of content is the application of a variable number of bytes as the measuring standard of the size of the content window. This variable size may be set as a function of several parameters, such as the size of the keyword list, the amount of data downloaded by the user, etc.

[0056] An advertisement selector unit in the server stores the browse history information received from the datastream scanner unit for each client session (step 712). The browse history information may include other information in addition to a generated list of keywords, such as URIs that identify the origin of the information constituting the datastream. This information is stored for later retrieval when the advertisement selector unit selects an appropriate advertisement to be sent to the client. The server then routes the modified HTTP response messages to the client (step 714).

[0057] With reference now to Figure 8, a flowchart describes a process in which a client scans an incoming datastream addressed to the client in order to generate browse history information that is transmitted back to a server. The process depicted in Figure 8 may be implemented by a client such as client 502 depicted in Figure 5. The process begins when the user selects a hyperlink or inputs a URI into the client browser (step 802). The client then sends HTTP request messages to the server along with browsing history information for the current session (step 804). The client then receives HTTP response messages from the server containing the previ-

ously requested information and including adaptively targeted advertisements placed into the HTTP response messages at appropriate locations in response to the browse history information previously sent from the client to the server (step 806). The client browser then displays the user requested information (step 808).

[0058] The methods by which the datastream scanner unit operates in Figures 7 and 8 may vary depending on a variety or combination of algorithms used to analyze the datastream. A datastream may be comprised of various types of information and information objects. When a datastream scanner unit scans a datastream, each portion of information in the datastream may be analyzed separately. For example, in a datastream consisting primarily of HTML Web pages, hyperlinks and markup tags may be analyzed separately from the ASCII text in the body of the pages.

[0059] As one example of the various processes that may be used to analyze a datastream, an adaptive weighting scheme may be employed that weights particular portions of the datastream more heavily than other portions, i.e. certain portions are considered to be more important than other portions in the determination of the gist of interest of the viewer. Hyperlink tags or text embodied inside HTML tags may be weighted more heavily than other types of text. If a viewer of a datastream were reading about swimsuits, and several of the links in the Web page contained URIs pointing to summer sports, island vacations, etc., then the scanner unit may weight the text in these links more heavily than other text. When the generated keyword list is used, advertisements will be chosen that are more directed to the content within the hyperlinks than in the body of the text. If a person is viewing Web pages by clicking through the hyperlinks, the advertisements which appear on the Web pages with these hyperlinks will possibly closely match the content that may appear on the Web pages that the person is preparing to view when a hyperlink is subsequently selected.

[0060] More particularly, if the scanner has analyzed the tags and found a word or set of words within URIs in the datastream, advertisers may be requested to pay higher advertisement rates to the ISP operating the server to insert particular advertisements targeted to particular URIs. Continuing with the previous example, a swimsuit manufacturer may pay a higher fee so that an advertisement for a swimsuit appears each time that a URI appears in the datastream containing the word stem "island," e.g., "http://www.greatvacations.com/islands." More complex formulas may be created for a more complex fee schedule. The session characterization information may be combined with the generated keyword list to form an effective manner of targeting advertisements. Using the previous example, the swimsuit manufacturer may be more willing to pay higher rates for the appearance of a URI with the word stem "island" if the session characterization information indicates that the person viewing the datastream lives in Hawaii rather

than Montana. Other information items that may be obtained in the session characterization information is explained in more detail further below.

**[0061]** Adaptively targeting advertisements through the use of URIs may be especially effective when the scanning is performed on the outgoing datastream, i.e., the datastream flowing from the client to the server and routed onto the Internet. The URIs in the HTTP request messages are the particular objects that a viewer has selected as being of immediate interest. When the words within these URIs are weighted more heavily than other words in the datastream, the generated keyword list can be more finely focused on the subsequently retrieved datastream, and the advertisements inserted into the datastream can be effectively targeted to the viewer's interest.

**[0062]** In addition to URIs, another portion of a datastream that may be weighted heavily is metadata or metainformation. Metadata is data that describes another, associated data item, i.e. information that provides characteristics about other information. Web pages constructed with HTML frequently contain META tags that contain metadata about the Web page in which the META tags are embedded. Since the content within META tags is not presented to the viewer of the Web page, these tags can contain any information that the author desires to store in a hidden manner. Some commercial Web search engines use the content within META tags for indexing a Web page.

**[0063]** In general, META tags contain a list of keywords and a short description of the content of the Web page, similar to an abstract. These keywords are chosen by the author or publisher of the Web page, and while the keywords may have been chosen arbitrarily, it may be assumed that the information within a META tag provides an accurate condensation of its associated content. Hence, content within a META tag would be an effective target for adaptive weighting. Since the datastream scanner unit attempts to generate a keyword list, a process that weights more heavily a keyword list or abstract that has already been embedded within a Web page than other portions of a Web page would be especially effective for targeting an advertisement that closely matches the context of the datastream.

**[0064]** Metadata may be placed in Internet-deliverable documents in a variety of manners. As another example besides HTML META tags, eXtensible Markup Language (XML) is being standardized to incorporate features for providing metadata. Meta Content Framework (MCF) and XML-Data are two proposals that incorporate the idea of metainformation into XML. Continuing with the point addressed above that many different types and sets of rules may be applied to the analysis of the datastream, a datastream scanner unit may combine rules for a moving window with rules for adaptive weighting. One manner of combining rules would be to introduce a temporal aspect to the weighting of keywords. Keywords that have been recently generated by

scanning a moving window of a datastream may be more heavily weighted than previously generated keywords. As previously generated keywords increase in age, their relative weighting diminishes.

**[0065]** With reference now to **Figure 9**, a flowchart depicts a process in which a server receives browse history information from a client and inserts adaptively targeted advertisements into the datastream sent back to the client. The process depicted in **Figure 9** may be implemented within a server, such as server **508** shown in **Figure 5**. The process begins when the server receives HTTP request messages from the client (step **902**). The server routes the HTTP request messages onto the Internet if necessary, or finds the requested information within the server (step **904**). The server also receives periodic reports of browse history information from the client (step **906**). The advertisement selector unit within the server stores the browse history information for each client session (step **908**). At some point, the server receives HTTP response messages from the Internet to be routed to the client in response to the original HTTP request messages (step **910**). The server then inserts adaptively targeted advertisements into appropriate locations within the HTTP response messages (step **912**). The server then routes the HTTP response messages to the client that include the adaptively targeted advertisements (step **914**).

**[0066]** With reference now to **Figure 10**, a flowchart depicts the process by which a server selects adaptively targeted advertisements based on the browsing history of a client. The process depicted in **Figure 10** may be similar to the process used by components within a server, such as server **408** shown in **Figure 4**.

**[0067]** The advertisement selector unit within the server receives a request from the advertisement inserter unit for an advertisement to be placed in the datastream for a particular client session (step **1002**). The advertisement selector unit retrieves previously stored browse history information for the particular client session (step **1004**). The advertisement selector unit also retrieves session characterization information (step **1006**). The advertisement selector unit then compares the list of keywords from the browse history information with previously stored keyword lists for categories of advertisements stored in the categorized advertisement database (step **1008**). The advertisement selector unit then compares the session characterization information against subcategory information for the set of advertisements in the previously selected category of advertisements (step **1010**).

**[0068]** The session characterization information may include types of information, such as: the type of computer platform that is being utilized as the client computer; the current time of day for the session between the client and the server; the current season of the year in which the session is being held; the amount of available connection bandwidth for the session; and the geographic location of the client computer. This type of in-

formation may narrow the choices for selecting an advertisement subcategory. For example, with a determination of a computer platform, such as an IBM compatible PC or an Apple Macintosh computer, more artistic advertisements may be directed towards the user of the Macintosh as the Macintosh is more prevalent within the desktop publishing industry. With respect to the time of day, business type advertisements may be directed to the user during the day while leisure or entertainment type advertisements are directed to a user in the evening. With respect to the season in which the session occurs, seasonal advertisements may be directed to a user, such as advertisements for skiing during the winter or advertisements for boating during the summer. With respect to the available connection bandwidth, an advertisement with simpler graphics may be directed to a user using a 56k modem while complex advertisements with MPEG movies may be directed to a user employing a cable modem. With respect to the location of the client computer, appropriate advertisement categories for the source of products and services may be determined based on whether the client computer is located in the north versus the south, east versus west, or rural versus urban locations.

**[0069]** The advertisement selector unit then selects an advertisement from the categorized advertisements database based on the results of these comparisons (step 1012). As noted above, advertisements may also be selected based on information in an advertiser database that generally describes the product or service offered by an advertiser or describes a general type of viewer that the advertiser is attempting to reach with targeted advertisements. The advertisement selector unit then sends the selected advertisement to the advertisement inserter unit (step 1014). The advertisement inserter unit then inserts the selected advertisement as an adaptively targeted advertisement into a modified HTTP response message to be routed to the client as part of the datastream address to the client (step 1016).

**[0070]** The process steps shown in Figure 10 may be modified so that the advertisement selection mechanism is essentially performed in the background and not in real time during the routing of the HTTP response messages constituting the datastream addressed to the client. In other words, when the advertisement selector unit receives the browse history information for a particular client session, in addition to storing the browse history information, the advertisement selector unit may begin the process of selecting an adaptively targeted advertisement for a client session without waiting for a request from the advertisement inserter unit. In this manner, the advertisement selector unit may have an appropriate advertisement or set of advertisements already selected for a particular client so that the advertisement inserter unit is not stalled waiting for a response from the advertisement selector unit.

**[0071]** Once the advertisement selector unit has selected an appropriate advertisement or advertisements

for a particular client session, it may store identification information for the selected advertisement(s) or a pointer(s) into the categorized advertisement database along with the stored browse history information within the advertisement selector unit. In this example, step 1002 in Figure 10 would be performed immediately before step 1014 so that any of the steps in the process for selecting an adaptively targeted advertisement have been previously performed, and the advertisement inserter unit may receive a quick response for identifying and inserting an advertisement into the datastream to be routed to the client.

**[0072]** With reference now to Figure 11, a flowchart depicts a process by which a server receives electronically published advertisements and processes these advertisements so that they may be retrieved at some later point as adaptively targeted advertisements. Figure 11 describes a process that may be performed by a data processing unit, such as advertisement processing unit 418 in Figure 4.

**[0073]** The distributed data processing system that includes the server establishing the browser session receives electronically published advertisements and stores them in a database containing unprocessed advertisements (step 1102). At some point, the advertisement processing unit retrieves the electronically published advertisement previously stored in the database of unprocessed advertisements (step 1104). The advertisement processing unit then generates a list of keywords for the retrieved advertisement derived from the content within the retrieved advertisement (step 1106). The advertisement processing unit then categorizes and subcategorizes the retrieved advertisement based on its generated list of keywords (step 1108). The advertisement processing unit then associatively stores the retrieved advertisement along with other electronically published and processed advertisements in the proper category and subcategory (step 1110). The advertisement selector unit on the server may later search and retrieve the processed advertisements from the categorized advertisement database (step 1112).

**[0074]** Thus, the present invention provides a method and apparatus for adaptively targeting advertisements to a particular user based on the user's browsing history. As the user browses the Internet, the user's datastream is analyzed for a set of keywords that represents a summary of the content that appears to be the focus of the interest of the user. Advertisements may be selected based on the summary of the interest of the user, and the advertisement may be placed into the datastream in a manner in which the advertisement closely resembles its surrounding context.

**[0075]** The present invention also provides a method for enticing Web viewers to look at adaptively targeted advertisements by giving something of monetary value to a viewer in exchange for looking at the advertisements. Once the viewer agrees to receive advertisements in a downloaded datastream, the online service

provider places advertisements into the viewer's datastream, and the viewer receives something of value in return, such as free online connection time, connection time at a reduced cost, or an acquired credit balance that may be applied to other purchases online. The online service provider or ISP receives revenues from advertisers for this particular service, presumably at a higher profit than the revenues that could be collected in connection fees from viewers. By knowing which viewers are looking at which advertisements, an advertiser may efficiently use advertising expenditures to target those viewers that are most likely to purchase the advertiser's products and services.

**[0076]** The advantages of the present invention should be readily apparent in reference to the description of the invention above. Without demographic information on the Web viewers visiting particular Web sites and domains, advertisers have merely relied upon the statistics related to the number of page views. An advertiser may then pay for the placement of advertisements based on the perception of the page traffic in which their advertisements may be placed. Advertisers may have also chosen the placement of advertisements based on the overall commercial aspect of a Web site or Web portal. With the use of the present invention, advertisements may be more intelligently directed towards the viewers of the advertisements in a manner in which a viewer may perceive an additional benefit by receiving advertisements that are related to a focus of interest. The present invention may provide the ability to direct advertisements more accurately than the method used in placing advertisements on broadcast or cable channels. In those cases, consumer research must be conducted after the broadcast to determine demographics of viewers that watched a particular broadcast. Through the use of the present invention, advertisements are blended into the content being viewed by a user on a real-time or near real-time basis.

**[0077]** It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media such a floppy disc, a hard disk drive, a RAM, and CD-ROMs and transmission-type media such as digital and analog communications links.

**[0078]** The description of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention,

the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

**[0079]** The embodiment is now described in clause form where each numbered paragraph represents a separate clause.

1. A method for providing online connection service from a server to a client in a distributed data processing system, the method comprising the computer-implemented steps of:

inserting selected advertisements into a datastream for a session connecting the server with the client; and  
reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream.

2. A method for providing online connection service from a server to a client in a distributed data processing system, the method comprising the computer-implemented steps of:

scanning, on the server, a datastream for a session connecting the server with the client;  
selecting advertisements based on the results of scanning the datastream;  
inserting the selected advertisements into the datastream; and  
reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream.

3. The method of clause 2 further comprising:  
computing a cost for the online connection service that is inversely proportional to a number of selected advertisements that are inserted into the datastream.

4. The method of clause 2 further comprising:

selecting, on the client, an option for disabling the insertion of the selected advertisements into the datastream;  
sending the selected option to the server;  
ceasing the insertion of selected advertisements into the datastream; and  
accounting for a cost for subsequent online connection service in a normal manner.

5. A method for sending advertisements from a server to a client in a distributed data processing system, the method comprising the computer-implemented steps of:

scanning, on the server, a datastream for a ses-

- sion connecting the server with the client;  
generating a list of keywords from content within the datastream;  
selecting advertisements based on the generated keyword list; and  
inserting the selected advertisements into the datastream. 5
6. The method of clause 5 wherein the step of scanning the datastream further comprises: 10  
storing the datastream as a cached datastream; and  
reading the cached datastream as input for scanning the datastream for the session. 15
7. The method of clause 5 wherein the content of the datastream comprises Uniform Resource Identifiers (URIs) and content within Hypertext Transport Control Protocol (HTTP) response messages received in response to HTTP requests directed to the URIs. 20
8. The method of clause 5 wherein the step of generating a list of keywords comprises deriving a list of keywords from a moving window of content within the datastream. 25
9. The method of clause 8 wherein the moving window of content is a variable number of downloaded Web pages. 30
10. The method of clause 8 wherein a size of the moving window of content is a variable number of bytes in the datastream. 35
11. The method of clause 8 wherein a size of the moving window is a function of a size of the keyword list. 40
12. The method of clause 5 wherein the step of generating a list of keywords further comprises compiling a list of keywords that most frequently occur within a variable amount of time within the session. 45
13. The method of clause 5 wherein the step of selecting advertisements further comprises:  
comparing the generated keyword list against a set of predetermined keyword lists, wherein each predetermined keyword list represents a category for a set of advertisements;  
determining a relative match as a result of the comparison; and  
selecting an advertisement from the set of advertisements in the matched category. 55
14. The method of clause 13 wherein the step of selecting advertisements further comprises:  
determining information that characterizes the session; and  
selecting an advertisement from the set of advertisements in a subcategory of the matched category based on the session characterization information.
15. The method of clause 14 wherein the session characterization information is selected from one or more types of information in a group comprising:  
a type of computer platform for the client;  
a current time of day for the session;  
a current season of the year for the session;  
an amount of connection bandwidth for the session; and a geographic location for the client.
16. The method of clause 5 wherein the step of selecting advertisements further comprises basing the selection on session characterization information selected from one or more types of information in a group comprising:  
a type of computer platform for the client;  
a current time of day for the session;  
a current season of the year for the session;  
an amount of connection bandwidth for the session; and  
a geographic location for the client.
17. The method of clause 5 wherein the step of generating a list of keywords further comprises:  
analyzing the datastream to identify a set of terms; and  
applying an adaptive weighting scheme in which a subset of terms in the set of terms are given greater emphasis as a keyword in the list of keywords.
18. The method of clause 7 wherein the content of the datastream comprises Uniform Resource Identifiers (URIs) and terms within the URIs are weighted with greater value than other terms not within the URIs.
19. The method of clause 17 wherein the content of the datastream comprises metadata, and wherein the metadata is weighted with greater value than other content in the datastream.
20. The method of clause 17 wherein the adaptive weighting of terms is a function of a time at which the terms appear in the datastream such that more recent terms are weighted more heavily than more distant terms.

21. A method for receiving advertisements at a client from a server in a distributed data processing system, the method comprising the computer-implemented steps of:

scanning, on the client, a datastream for a session connecting the client with the server;  
generating a list of keywords from content within the datastream;  
sending the generated list of keywords to the server; and  
receiving advertisements within the datastream, wherein the advertisements comprise content semantically related to the generated list of keywords.

22. The method of clause 21 further comprising:  
caching advertisements placed as hidden advertisement content within markup language tags in the datastream, wherein the hidden advertisement content is not displayed by the browser when a markup language document containing the hidden advertisement content is displayed.

23. The method of clause 22 further comprising:  
retrieving the hidden advertisement content during periods of user inactivity; and  
displaying advertisements derived from the hidden advertisement content on a display device of the client.

24. A distributed data processing system for providing online connection service from a server to a client, the distributed data processing system comprising:

inserting means for inserting selected advertisements into a datastream for a session connecting the server with the client; and  
reducing means for reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream.

25. A distributed data processing system for providing online connection service from a server to a client, the distributed data processing system comprising:

scanning means for scanning, on the server, a datastream for a session connecting the server with the client;  
selecting means for selecting advertisements based on the results of scanning the datastream;  
inserting means for inserting the selected advertisements into the datastream; and

reducing means for reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream.

26. The data processing system of clause 25 further comprising:

computing means for computing a cost for the online connection service that is inversely proportional to a number of selected advertisements that are inserted into the datastream.

27. The data processing system of clause 25 further comprising:

selecting means for selecting, on the client, an option for disabling the insertion of the selected advertisements into the datastream;  
sending means for sending the selected option to the server;  
ceasing means for ceasing the insertion of selected advertisements into the datastream; and  
accounting means for accounting for a cost for subsequent online connection service in a normal manner.

28. A distributed data processing system for sending advertisements from a server to a client, the distributed data processing system comprising:

scanning means for scanning, on the server, a datastream for a session connecting the server with the client;  
generating means for generating a list of keywords from content within the datastream;  
selecting means for selecting advertisements based on the generated keyword list; and  
inserting means for inserting the selected advertisements into the datastream.

29. The data processing system of clause 28 wherein the scanning means for scanning the datastream further comprises:

storing means for storing the datastream as a cached datastream; and  
reading means for reading the cached datastream as input for scanning the datastream for the session.

30. The data processing system of clause 28 wherein the content of the datastream comprises Uniform Resource Identifiers (URIs) and content within Hypertext Transport Control Protocol (HTTP) response messages received in response to HTTP requests directed to the URIs.

31. The data processing system of clause 28

wherein the generating means for generating a list of keywords comprises deriving means for deriving a list of keywords from a moving window of content within the datastream.

5

32. The data processing system of clause 31 wherein the moving window of content is a variable number of downloaded Web pages.

33. The data processing system of clause 31 wherein a size of the moving window of content is a variable number of bytes in the datastream.

10

34. The data processing system of clause 31 wherein a size of the moving window is a function of a size of the keyword list.

15

35. The data processing system of clause 28 wherein the generating means for generating a list of keywords further comprises compiling means for compiling a list of keywords that most frequently occur within a variable amount of time within the session.

20

36. The data processing system of clause 28 wherein the selecting means for selecting advertisements further comprises:

25

comparing means for comparing the generated keyword list against a set of predetermined keyword lists, wherein each predetermined keyword list represents a category for a set of advertisements;  
determining means for determining a relative match as a result of the comparison; and  
selecting means for selecting an advertisement from the set of advertisements in the matched category.

30

35

37. The data processing system of clause 36 wherein the selecting means for selecting advertisements further comprises:

40

determining means for determining means for determining information that characterizes the session; and  
selecting means for selecting an advertisement from the set of advertisements in a subcategory of the matched category based on the session characterization information.

45

50

38. The data processing system of clause 37 wherein the session characterization information is selected from one or more types of information in a group comprising:

55

a type of computer platform for the client;  
a current time of day for the session;

a current season of the year for the session;  
an amount of connection bandwidth for the session; and  
a geographic location for the client.

39. The data processing system of clause 28 wherein the selecting means for selecting advertisements further comprises selecting means for basing the selection on session characterization information selected from one or more types of information in a group comprising:

a type of computer platform for the client;  
a current time of day for the session;  
a current season of the year for the session;  
an amount of connection bandwidth for the session; and  
a geographic location for the client.

40. The data processing system of clause 28 wherein the generating means for generating a list of keywords further comprises:

analyzing means for analyzing the datastream to identify a set of terms; and  
applying means for applying an adaptive weighting scheme in which a subset of terms in the set of terms are given greater emphasis as a keyword in the list of keywords.

41. The data processing system for clause 40 wherein the content of the datastream comprises Uniform Resource Identifiers (URIs) and terms within the URIs are weighted with greater value than other terms not within the URIs.

42. The method of clause 40 wherein the content of the datastream comprises metadata, and wherein the metadata is weighted with greater value than other content in the datastream.

43. The method of clause 40 wherein the adaptive weighting of terms is a function of a time at which the terms appear in the datastream such that more recent terms are weighted more heavily than more distant terms.

44. A distributed data processing system for receiving advertisements at a client from a server, the distributed data processing system comprising:

scanning means for scanning, on the client, a datastream for a session connecting the client with the server;  
generating means for generating a list of keywords from content within the datastream;  
sending means for sending the generated list of keywords to the server; and



receiving means for receiving advertisements within the datastream, wherein the advertisements comprise content semantically related to the generated list of keywords.

45. The data processing system of clause 44 further comprising:

caching means for caching advertisements placed as hidden advertisement content within markup language tags in the datastream, wherein the hidden advertisement content is not displayed by the browser when a markup language document containing the hidden advertisement content is displayed.

46. The data processing system of clause 45 further comprising:

retrieving means for retrieving the hidden advertisement content during periods of user inactivity; and

displaying means for displaying advertisements derived from the hidden advertisement content on a display device of the client.

47. A computer program product in a computer readable medium for use in a distributed data processing system for providing online connection service from a server to a client, the computer program product comprising:

first instructions for inserting selected advertisements into a datastream for a session connecting the server with the client; and  
second instructions for reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream.

48. A computer program product in a computer readable medium for use in a distributed data processing system for providing online connection service from a server to a client, the computer program product comprising:

first instructions for scanning, on the server, a datastream for a session connecting the server with the client;  
second instructions for selecting advertisements based on the results of scanning the datastream;  
third instructions for inserting the selected advertisements into the datastream; and  
fourth instructions for reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream.

49. The computer program product of clause 48 further comprising:

instructions for computing a cost for the online connection service that is inversely proportional to a number of selected advertisements that are inserted into the datastream.

50. The computer program product of clause 48 further comprising:

instructions for selecting, on the client, an option for disabling the insertion of the selected advertisements into the datastream;  
instructions for sending the selected option to the server;  
instructions for ceasing the insertion of selected advertisements into the datastream; and  
instructions for accounting for a cost for subsequent online connection service in a normal manner.

51. A computer program product in a computer-readable medium for use in a distributed data processing system for sending advertisements from a server to a client, the computer program product comprising:

first instructions for scanning, on the server, a datastream for a session connecting the server with the client;  
second instructions for generating a list of keywords from content within the datastream;  
third instructions for selecting advertisements based on the generated keyword list; and  
fourth instructions for inserting the selected advertisements into the datastream.

52. The computer program product of clause 51 wherein the first instructions for scanning the datastream further comprises:

instructions for storing the datastream as a cached datastream; and  
instructions for reading the cached datastream as input for scanning the datastream for the session.

53. The computer program product of clause 51 wherein the content of the datastream comprises Uniform Resource Identifiers (URIs) and content within Hypertext Transport Control Protocol (HTTP) response messages received in response to HTTP requests directed to the URIs.

54. The computer program product of clause 51 wherein the second instructions for generating a list of keywords comprises instructions for deriving a list of keywords from a moving window of content

within the datastream.

55. The computer program product of clause 54 wherein the moving window of content is a variable number of downloaded Web pages.

5

56. The computer program product of clause 54 wherein a size of the moving window of content is a variable number of bytes in the datastream.

10

57. The computer program product of clause 54 wherein a size of the moving window is a function of a size of the keyword list.

58. The computer program product of clause 51 wherein the second instructions for generating a list of keywords further comprises instructions for compiling a list of keywords that most frequently occur within a variable amount of time within the session.

15

20

59. The computer program product of clause 51 wherein the third instructions for selecting advertisements further comprises:

instructions for comparing the generated keyword list against a set of predetermined keyword lists, wherein each predetermined keyword list represents a category for a set of advertisements;

25

instructions for determining a relative match as a result of the comparison; and

30

instructions for selecting an advertisement from the set of advertisements in the matched category.

35

60. The computer program product of clause 59 wherein the instructions for selecting an advertisement from the set of advertisements in the matched category further comprises:

instructions for determining information that characterizes the session; and

40

instructions for selecting an advertisement from the set of advertisements in a subcategory of the matched category based on the session characterization information.

45

61. The computer program product of clause 60 wherein the session characterization information is selected from one or more types of information in a group comprising:

50

a type of computer platform for the client;

a current time of day for the session;

a current season of the year for the session;

55

an amount of connection bandwidth for the session; and

a geographic location for the client.

62. The computer program product of clause 51 wherein the third instructions for selecting advertisements further comprises instructions for basing the selection on session characterization information selected from one or more types of information in a group comprising:

a type of computer platform for the client;

a current time of day for the session;

a current season of the year for the session;

an amount of connection bandwidth for the session; and

a geographic location for the client.

63. The computer program product of clause 51 wherein the second instructions for generating a list of keywords further comprises:

instructions for analyzing the datastream to identify a set of terms; and

instructions for applying an adaptive weighting scheme in which a subset of terms in the set of terms are given greater emphasis as a keyword in the list of keywords.

64. The computer program product of clause 63 wherein the content of the datastream comprises Uniform Resource Identifiers (URIs) and terms within the URIs are weighted with greater value than other terms not within the URIs.

65. The computer program product of clause 63 wherein the content of the datastream comprises metadata, and wherein the metadata is weighted with greater value than other content in the datastream.

66. The computer program product of clause 63 wherein the adaptive weighting of terms is a function of a time at which the terms appear in the datastream such that more recent terms are weighted more heavily than more distant terms.

67. A computer program product for receiving advertisements at a client from a server in a distributed data processing system, the computer program product comprising:

first instructions for scanning, on the client, a datastream for a session connecting the client with the server;

second instructions for generating a list of keywords from content within the datastream;

third instructions for sending the generated list of keywords to the server; and

fourth instructions for receiving advertisements within the datastream, wherein the advertisements comprise content semantically related to

the generated list of keywords.

68. The computer program product of clause 67 further comprising:

instructions for caching advertisements placed as hidden advertisement content within markup language tags in the datastream, wherein the hidden advertisement content is not displayed by the browser when a markup language document containing the hidden advertisement content is displayed.

69. The computer program product of clause 68 further comprising:

instructions for retrieving the hidden advertisement content during periods of user inactivity; and  
instructions for displaying advertisements derived from the hidden advertisement content on a display device of the client.

[0080] In summary a method and apparatus for adaptively targeting advertisements to a specific client computer from a server within a distributed data processing system is provided. As a user of the client browses the World Wide Web, the material that is downloaded to the client constitutes a datastream. At some location during the routing of the datastream, either on the server or at the client, the datastream is scanned to generate a list of keywords that are present within the datastream. The datastream may be analyzed in real-time or cached and analyzed on a delayed basis. The generated list of keywords represents a summary of the content that appears to be the focus of interest of the user. The keywords are compared against a database of advertisements, and the server selects an advertisement that matches the user's area of interest in comparison to the analysis of the user's browsing history. The selected advertisement is then inserted into the datastream to be routed to the client. In consideration for viewing targeted advertisements and to entice a Web viewer to allow the monitoring of a datastream so that targeted advertisements may be placed into the datastream, a Web viewer may receive online connection service for free, for a reduced cost, at a premium level of service, or for other some other value, such as frequent viewer credits that may be exchanged for goods and services.

#### Claims

1. A method for providing online connection service from a server to a client in a distributed data processing system, the method comprising the computer-implemented steps of:

inserting selected advertisements into a data-

stream for a session connecting the server with the client; and

reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream.

2. A method of claim 1 further comprising the steps of:

scanning, on the server, the datastream for a session connecting the server with the client; and

selecting advertisements based on the results of scanning the datastream.

3. The method of claim 2 further comprising:

computing a cost for the online connection service that is inversely proportional to a number of selected advertisements that are inserted into the datastream.

4. The method of claim 2 further comprising:

selecting, on the client, an option for disabling the insertion of the selected advertisements into the datastream;

sending the selected option to the server;

ceasing the insertion of selected advertisements into the datastream; and

accounting for a cost for subsequent online connection service in a normal manner.

5. A method for sending advertisements from a server to a client in a distributed data processing system, the method comprising the computer-implemented steps of:

scanning, on the server, a datastream for a session connecting the server with the client;

generating a list of keywords from content within the datastream;

selecting advertisements based on the generated keyword list; and

inserting the selected advertisements into the datastream.

6. The method of claim 5 wherein the step of scanning the datastream further comprises:

storing the datastream as a cached datastream; and

reading the cached datastream as input for scanning the datastream for the session.

7. The method of claim 5 wherein the content of the datastream comprises Uniform Resource Identifiers (URIs) and content within Hypertext Transport Control Protocol (HTTP) response messages received in response to HTTP requests directed to the URIs. 5
8. The method of claim 5 wherein the step of generating a list of keywords comprises deriving a list of keywords from a moving window of content within the datastream. 10
9. The method of claim 8 wherein the moving window of content is a variable number of downloaded Web pages. 15
10. The method of claim 8 wherein a size of the moving window of content is one or more of: 20
  - (i) a variable number of bytes in the datastream;
  - (ii) a function of a size of the keyword list. 25
11. The method of claim 5 wherein the step of selecting advertisements further comprises:
  - comparing the generated keyword list against a set of predetermined keyword lists, wherein each predetermined keyword list represents a category for a set of advertisements; 30
  - determining a relative match as a result of the comparison; and 35
  - selecting an advertisement from the set of advertisements in the matched category. 40
12. A distributed data processing system for providing online connection service from a server to a client, the distributed data processing system comprising:
  - inserting means for inserting selected advertisements into a datastream for a session connecting the server with the client; and 45
  - reducing means for reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream. 50
13. A distributed data processing system for sending advertisements from a server to a client, the distributed data processing system comprising: 55
  - scanning means for scanning, on the server, a

datastream for a session connecting the server with the client;

generating means for generating a list of keywords from content within the datastream;

selecting means for selecting advertisements based on the generated keyword list; and

inserting means for inserting the selected advertisements into the datastream.

14. A distributed data processing system for receiving advertisements at a client from a server, the distributed data processing system comprising:

scanning means for scanning, on the client, a datastream for a session connecting the client with the server;

generating means for generating a list of keywords from content within the datastream;



sending means for sending the generated list of keywords to the server; and

receiving means for receiving advertisements within the datastream, wherein the advertisements comprise content semantically related to the generated list of keywords.

15. A computer program product in a computer readable medium for use in a distributed data processing system for providing online connection service from a server to a client, the computer program product comprising:

first instructions for inserting selected advertisements into a datastream for a session connecting the server with the client; and

second instructions for reducing a cost for the online connection service in response to the insertion of the selected advertisements into the datastream.






FIG. 3




FIG. 4






FIG. 5






FIG. 11

FIG. 9






FIG. 10



(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 1 061 465 A3**

(12)

**EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
02.01.2003 Bulletin 2003/01

(51) Int Cl.7: G06F 17/60, G06F 17/30

(43) Date of publication A2:  
20.12.2000 Bulletin 2000/51

(21) Application number: 00305103.4

(22) Date of filing: 16.06.2000

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:

- Berstis, Viktors, IBM United Kingdom Ltd.  
Winchester, Hampshire SO21 2JN (GB)
- Rodriguez, Herman, IBM United Kingdom Ltd.  
Winchester, Hampshire SO21 2JN (GB)

(30) Priority: 17.06.1999 US 335287

(74) Representative: Waldner, Philip  
IBM United Kingdom Limited,  
Intellectual Property Department,  
Hursley Park  
Winchester, Hampshire SO21 2JN (GB)

(71) Applicant: International Business Machines  
Corporation  
Armonk, NY 10504 (US)

(54) **Method and apparatus for providing reduced cost online service and adaptive targeting of advertisements**

(57) A method and apparatus for adaptively targeting advertisements to a specific client computer from a server within a distributed data processing system is provided. As a user of the client browses the World Wide Web, the material that is downloaded to the client constitutes a datastream. At some location during the routing of the datastream, either on the server or at the client, the datastream is scanned to generate a list of key-words that are present within the datastream. The datastream may be analyzed in real-time or cached and analyzed on a delayed basis. The generated list of key-words represents a summary of the content that appears to be the focus of interest of the user. The key-

words are compared against a database of advertisements, and the server selects an advertisement that matches the user's area of interest in comparison to the analysis of the user's browsing history. The selected advertisement is then inserted into the datastream to be routed to the client. In consideration for viewing targeted advertisements and to entice a Web viewer to allow the monitoring of a datastream so that targeted advertisements may be placed into the datastream, a Web viewer may receive online connection service for free, for a reduced cost, at a premium level of service, or for other some other value, such as frequent viewer credits that may be exchanged for goods and services.




FIG. 4



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 00 30 5103

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 901 287 A (CARR JR ROBERT NEAL ET AL) 4 May 1999 (1999-05-04)	1-3,5-15	G06F17/60 G06F17/30
Y	* column 3, line 21 - column 5, line 32 * * column 6, line 16 - column 8, line 36 * * column 10, line 32 - column 11, line 28 * * column 13, line 32 - column 14, line 9 * * figures 1,6 *	4	
X	KOHDA Y ET AL: "UBIQUITOUS ADVERTISING ON THE WWW: MERGING ADVERTISEMENT ON THE BROWSER" COMPUTER NETWORKS AND ISDN SYSTEMS, NORTH HOLLAND PUBLISHING. AMSTERDAM, NL, vol. 28, 1 May 1996 (1996-05-01), pages 1493-1499, XP002037594 ISSN: 0169-7552	1,12,15	
Y	* abstract; figure 2 * * page 1494, column 1, paragraph 3 - page 1498, column 2, paragraph 5 *	4	
X	WO 97 21183 A (BELL COMMUNICATIONS RES) 12 June 1997 (1997-06-12) * abstract * * page 3, line 8 - page 10, line 25 * -/--	1,12,15	TECHNICAL FIELDS SEARCHED (Int.Cl.7) G06F
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 31 October 2002	Examiner Hopper, E
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03 82 (P04C01)



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 00 30 5103

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	KHAN I ET AL: "Categorizing Web documents using competitive learning: an ingredient of a personal adaptive agent" NEURAL NETWORKS,1997., INTERNATIONAL CONFERENCE ON HOUSTON, TX, USA 9-12 JUNE 1997, NEW YORK, NY, USA,IEEE, US, 9 June 1997 (1997-06-09), pages 96-99, XP010238799 ISBN: 0-7803-4122-8 * abstract; figure 1 * * page 96, column 2, paragraphs 2,3 * * page 97, column 1, paragraph 1 - column 2, paragraph 1 *	5-9	
A	US 5 848 396 A (GERACE THOMAS A) 8 December 1998 (1998-12-08) * abstract; figure 2 * * column 2, line 3 - column 3, line 19 * * column 4, line 1 - column 5, line 40 *	1,5, 12-15	
P,X	US 6 044 376 A (KURTZMAN II STEPHEN J) 28 March 2000 (2000-03-28) * abstract; figure 1 * * column 2, line 52 - column 4, line 61 *	1,2,5-15	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
Place of search MUNICH		Date of completion of the search 31 October 2002	Examiner Hopper, E
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (3.82) (F04C01)



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 30 5103

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

31-10-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5901287	A	04-05-1999	AU 7111496 A	22-10-1997
			WO 9737314 A1	09-10-1997
			US 5995943 A	30-11-1999
			US 6208975 B1	27-03-2001
			ZA 9610795 A	27-06-1997
WO 9721183	A	12-06-1997	CA 2240009 A1	12-06-1997
			EP 0954797 A1	10-11-1999
			JP 2001525951 T	11-12-2001
			WO 9721183 A1	12-06-1997
US 5848396	A	08-12-1998	CA 2252568 A1	06-11-1997
			EP 0895685 A2	10-02-1999
			WO 9741673 A2	06-11-1997
			US 5991735 A	23-11-1999
US 6044376	A	28-03-2000	NONE	

EPO FORM P459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82